

cube2mseed(1)

Name

cube2mseed - convert Cube data to miniSEED format

Synopsis

```
cube2mseed [-v|--verbose] [--include-pattern=PATTERN]...  
            [--trace-start=TIMEMOMENT] [--trace-stop=TIMEMOMENT]  
            [--trace-length=DURATION] [--trace-offset=SHIFT]  
            [--events=EVENTFILE] [--wnro-correction=AUTO|OFF|FORCE]  
            [--timing-control=ALGORITHM] [--fringe-samples=MODE]  
            [--resample=ALGORITHM] [--byte-order=ORDER]  
            [--record-size=N] [--encoding=CODEC]  
            [--output-dir=DIRECTORY] [--force-overwrite]]  
            file | directory...
```

```
cube2mseed [-h|--help] [--version] [--sysinfo]
```

Description

The **cube2mseed** utility reads Cube data from one or more *files* and converts them to miniSEED format. If an input *directory* is given as argument, **cube2mseed** searches recursively for Cube files inside the directory. The search can be shortened to contain only files with a name matching patterns given by the **--include-pattern** option.

After the initial search for available Cube files completed, the program will begin to index the data contained in the respective files. This step is necessary so that the program later knows of all Cube files belonging to the same continuous trace and about the correct chronological order.

As soon as the end of a continuous time series is detected, the utility will begin to work through the (internal) lists of time windows that were requested by the user via the options **--events**, **--trace-start**, **--trace-stop**, etc. The required samples are read from the Cube files, resampled and converted to the miniSEED format. Finally, the result is written directly to standard output (i.e. console) or saved in an output directory (use option **--output-dir**). **Cube2mseed** then turns back again to scanning through the Cube input for more continuous recordings, processing one trace after another.

Options

The program pretty much follows expected Unix command line syntax. Some command line

options have two variants, one long and an additional short one (for convenience). These are shown below, separated by commas. However, most options only have a long variant. The '=' for options that take a parameter is required and cannot be replaced by a whitespace.

-h, --help

Summarize the most important command line options and exit.

--version

Print the **cube2mseed** release information and exit.

--sysinfo

Report system settings relevant for **cube2mseed** and exit.

-v, --verbose

This option increases the amount of information given to the user during program execution. By default, (i.e. without this option) **cube2mseed** only reports warnings and errors. (See the diagnostics section below.)

--include-pattern=PATTERN

Only process files whose filename matches the given *PATTERN*. Files with a name not matching the search *PATTERN* will be ignored. This option is useful to speed up recursive searches through large subdirectory trees and can be used more than once in the same command line. (In this case files matching any of the provided patterns are included.)

You can use two wild card characters (***** and **?**) when specifying an include *PATTERN*. For example using **'*.123'** selects all files ending with the extension **.123**. Remember to enclose patterns with single quotes when using wildcards or spaces in the context of an **--include-pattern** command line option.

There is also a predefined GIPP filter. Using **--include-pattern=GIPP** automatically selects all data files following the default naming convention for files recorded by loggers borrowed from the Geophysical Instrument Pool Potsdam (GIPP).



The search *PATTERN* is only applied to the filename part and not to the full pathname of a file.

The following command line options are all used to specify an input time window for reading data from the Cube files. It is considered an error to use **--trace-start**, **--trace-stop** and **--trace-length** all at the same time. At most two of the three options may be used together. Also, the option **--trace-length** cannot be used alone. It needs a **--trace-start** or **--trace-stop** as anchor.

--trace-start=TIMEMOMENT

Begin converting Cube data at this moment in time. The format for the *TIMEMOMENT* string is **YYYY-MM-DDTHH:MM:SS.ssssss** where **YYYY-MM-DD** represents the date and **HH:MM:SS.ssssss** the time (fractions of seconds will be rounded to microsecond accuracy). The letter **T** in between date and time is used to distinguish between date and time part and must be given as well.

Example: To begin reading samples at 1pm on March 27th, 2007 use the *TIMEMOMENT* string **--trace-start=2007-03-27T13:00:00**.

--trace-stop=TIMEMOMENT

Stop processing time series data after this moment in time. The format for the *TIMEMOMENT* string is the same as with the **--trace-start** option.

--trace-length=DURATION

Stop processing samples after this time span. The *DURATION* is given in seconds and formatted as SS.ssssss. Again, fractions of seconds will be rounded to microsecond accuracy.

Example: To extract 10 minutes of data use **--trace-length=600**.

A trace length of 5 minutes will be used as default setting if no trace length option is given but a singular **--trace-start** or **--trace-stop** option is encountered.

--trace-offset=SHIFT

Use this option to shift the whole time window defined by the command line options above. This option exists purely for convenience reasons as it would be easy to have the same effect by adding *SHIFT* seconds to the trace start and stop times manually. In other words, using **--trace-offset** just spares you doing the math when you have a list of event times (e.g. from an earthquake catalog) but would like to extract a few seconds of data before the event as well.

The format of the trace offset value is SS.ssssss, which is given in seconds. Negative number shift the window towards earlier times, positive number "delay" the window. The total length of the time window is not affected by this option.

--events=EVENTFILE

In addition to the four time window options described above, it is also possible to use an event file to define many time windows all at once. Using an event file makes it possible to convert more than one time window per program run. Each line in the event file must begin with the start time of a time window that should be converted to miniSEED format. Optionally, the length and offset of the time window may follow in the second and third column.

The event file contains up to three columns separated by spaces or tabulators. The three columns are:

Column #1

Start time of the time window. Analog to the **--trace-start** command line option. This column is mandatory.

Column #2

Length of the time window. Analog to the **--trace-length** command line option. If this column is missing a (default) trace length of 2 minutes is processed.

Column #3

An additional shift/offset is applied to the time window. Analog to the **--trace-offset** command line option. This column is also optional.

Empty lines in the file are ignored. Everything following a # character (up to the end of the line) is considered to be a comment and is skipped as well. Columns are counted from the beginning of the line. This means you cannot define a trace offset (column #3) without having a trace

length (column #2) in the line first!



The use of an event file is completely independent of the trace start, stop, length or offset command line options. Especially, the `--trace-length` option only applies to time windows given via `--trace-start` or `--trace-stop` but never to time windows defined inside an event file!

Ignoring the implementation details of Cube file format, Cube recordings basically consist of a continuous stream of sample (amplitude) values, where occasional a single sample is additionally timestamped with the precise time of its recording (taken from GPS). The following command line options are used to control how the time information contained in the Cube files is transported into the miniSEED file format.

`--wnro-correction=`*AUTO* | *OFF* | *FORCE*

Data loggers receive the recording time from the Global Positioning System (*GPS*). Unlike the commonly used Gregorian calendar, *GPS* (internally) expresses date/time information using two integer numbers. The first number counts the weeks since start of the *GPS* system on January 6th, 1980. The second number gives the seconds relative to the beginning of the week.

Satellites transmit the week number as a 10-bit long integer, which will become zero again every 1024 weeks. This integer overflow is called week number rollover (*WNRO*) and is a common issue with all GPS receivers.

Usually, the **cube2mseed** utility will detect *WNRO* and just correct the date automatically by adding 1024 weeks to the "wrong" recording time. However, in cases where the automatic detection and correction fails, the handling of *WNRO* can be manually controlled using this command line option.

AUTO

Automatically detect and correct *WNRO* problems. This is the default mode.

OFF

Disable any (automatic) *WNRO* corrections for the input data. Time information will be used as recorded by the GPS receiver.

FORCE

Force apply *WNRO* corrections to the input data.

Please note that the `--wnro-correction` option only affects the handling of *WNRO* caused errors. General quality control of the timing accuracy can independently be adjusted using the `--timing-control` command line option.



Unless there is a good reason for it, the "*WNRO* correction" should be left in the default automatic mode. Use *OFF* or *FORCE* arguments to overwrite in case the automatic *WNRO* detection fails.

`--timing-control=`*ALGORITHM*

Cube data loggers keep track of the time by tagging selected sample values with precise time

information. These (time) tagged samples are the foundation of the overall timing accuracy of the recording. To ensure a high precision it is essential to verify the integrity and premium of the recorded time tags. Use this option to select one of the following quality control algorithms:

LLS

Compute a "local least squares" (LLS) approximation to detect outliers and other dubious time information.

The algorithm will determine the timing quality from the squared residual error ("misfit") of an individual time tag compared to a fitted line through the respective surrounding time tags. Any unexpected large misfit is a good indicator for the presence of a "bad" time tag (e.g. an outlier). All suspicious time tags are excluded from further processing.

This is the default timing quality control algorithm.

RULE

Do a rule-based evaluation of the time tags. The rules are predefined and hard-coded into the program. They were determined by trial and error.

NONE

Skip quality control altogether! This will use any available timing information without further qualification.

FAKE

This "quality control" algorithm will completely overwrite any time information recorded in a Cube trace with a made-up fake time. (All trace start times are set to 1970-01-01 00:00.) Obviously, this will completely screw up the timing information! Use it at your own risk.



Using the *FAKE* time algorithm will only succeed if the `--fringe -samples=NOMINAL` command line option is used as well.

The main advantage of the *LLS* algorithm is its flexibility. It was designed to adapt to different situations and to handle different time keeping hardware as well. The *RULE* based algorithm is faster and much simpler. However, the fixed rule set only works effectively for anticipated situations and is limited to the current build-in and well-known GPS hardware. Future Cube generations e.g. will probably require an updated set of rules to reliably detect bad time tags due to different time keeping hardware. The *NONE* "algorithm" basically disables any timing quality control. It should only be used if you can trust all time tags unconditionally (or do not care). Finally, the *FAKE* time algorithm is intended for worst case scenarios only, where a user absolutely must recover a Cube data stream that cannot be processed normally due to total lack of (recorded) timing information. By adding a fake time the Cube file(s) becomes "processable" again, although at the price of a completely made-up time information.

In addition to the above listed algorithms, recorded time tags are also screened for overall data integrity (range check, checksum) and completeness. Also, there is a certain hardware limitation common to all recorders of the Cube family that occasionally cause individual time tags to be discarded. This is done transparently in the background and before any of the above algorithms are applied. This cannot be influenced by the user!

--fringe-samples=MODE

Determines how to treat samples that were recorded before the first GPS time fix or after the last GPS time fix taken by the Cube unit. Determining the precise recording time of these "fringe samples" is problematic because without a second time tag on the other side of the sample, the precise sampling rate inside the segment cannot be computed. Valid options are:

SKIP

Simply exclude all samples without good time control from the conversion. (Default)

NOMINAL

Include fringe samples assuming a perfect nominal sample rate (e.g. 50 Hz, 100 Hz, 200 Hz, ...; as configured in the Cube recorder setup).

CONSTANT

Include fringe samples assuming a constant (linear) clock drift over the whole recording. The clock drift is calculated from the very first and last available GPS fix in the recording.

Usually, a Cube recording contains only a few seconds of data before the very first GPS time fix occurs. At the end of recording, the time without GPS fix depends on the recorder configuration. (GPS running continuous or in cycled mode? How long is the cycle?) So, unless you power down and pick up the Cube unit immediately after the recording there should be no problem to just skip and ignore all fringe samples, which is the default behavior.

The situation is different however, when the Cube is deployed in locations without (reliable) GPS reception, e.g. in water or underground in a tunnel. Especially, if the Cube runs out of power before it can obtain a last GPS fix. Here it might become important to include any recorded sample despite the lack of good (GPS) time control. For these cases the *NOMINAL* and *CONSTANT* mode are intended.

--resample=ALGORITHM

The sampling rate at which a Cube records data is derived from a build-in, high precision crystal oscillator. But despite using high-quality components, a tiny arbitrary offset from its nominal frequency remains. Causes for the offset include e.g. component aging and changes in temperature that alter the piezoelectric effect in the crystal oscillator. Unfortunately, this results in a slightly varying sampling rate during the recording that needs to be compensated by resampling the time series. This command line option selects the resampling algorithm.



It is highly recommended that you stick to the default *SINC* algorithm unless you have special needs and know what you do!

SINC

Resample the Cube data using a windowed *sinc* interpolation with a normalized Blackmann-Nuttall window. By default, the window width is set to 25. (Resulting in a filter kernel of $2 \times 25 + 1 = 51$ points.)

The width of the Blackmann-Nuttall window can be adjusted by appending the desired width to the *SINC* keyword (separated by a single comma; no spaces). Please see below for an example.

LINEAR

Use a basic linear interpolation between samples.

NONE

Simply copy the Cube input time series to the output without any modification to the sample amplitudes at all! The only modification done by this algorithm is to (slightly) shift the samples along the time axis. The recording time of the very first sample will be used as start time of the time series. All following samples will be time shifted such that a "perfect" sample period results. Obviously, the absolute timing error increases as the converted time series grows in length!



This *NONE* "resampler" simply *fudges the recording time* of the input samples! There is absolutely no resampling done by this algorithm (in a mathematical sense).

It was added to the program solely to provide some backward compatibility to earlier versions of **cube2mseed**, before proper resampling was implemented (i.e. all GIPPtool releases before 2014). Please see below for an example on how to replicate the old behavior. Nevertheless, its usage is highly discouraged!

The remaining command line arguments control the output of **cube2mseed** utility. An output directory can be selected to which the converted time series data is written. Other arguments are provided to select the specific formatting variant used for writing.

--output-dir=DIRECTORY

Save the resulting miniSEED files to this *DIRECTORY*. The directory must already exist and be writable! Already existing files in that directory will not be overwritten unless the option **--force-overwrite** is used as well.

--force-overwrite

If this option is used, already existing files in the output directory will be overwritten without mercy!

The default behavior, however, is **not** to overwrite already existing files. Instead, a new file is created with an additional number before the file extension.

--byte-order=ORDER

Set the byte order used for the miniSEED output. Valid values are *BIG_ENDIAN* or *LITTLE_ENDIAN*, each selecting the respective byte order. Using the (default) value *NATIVE* as argument automatically changes the byte order to the native byte order of the used computer platform (e.g. little endian on Intel PCs and big endian on Sun SPARC machines).

--record-size=N

Set the record size of the miniSEED output. The record size is given in bytes and must be a power of two value (e.g. 512, 1024, 2048, ...). By default, 4096 byte long records are written.

--encoding=CODEC

Set the encoding scheme for the time series data. The following encoding schemes are

supported:

INT-32

Uncompressed 32-bit integers.

FLOAT-32

Uncompressed IEEE single precision (32-bit) floating-point numbers.

FLOAT-64

Uncompressed IEEE double precision (64-bit) floating-point numbers.

STEIM-1

Steim-1 compressed integers (default).

STEIM-2

Steim-2 compressed integers.

Environment

The following environment variables can optionally be used to influence the behavior of the GIPPTool utilities.

GIPPTOOLS_HOME

This environment variable can be used to set the GIPPTools installation directory.

In particular, the Java classes that make up the GIPPTools are read from *JAR* files in the **java** subdirectory located inside **GIPPTOOLS_HOME**. The start scripts for the individual GIPPTool utilities can be found inside the **bin** subdirectory.

GIPPTOOLS_JAVA

The utilities of the GIPPTools are written in the programming language Java and consequently need a Java Runtime Environment (*JRE*) to execute. Use this variable to specify the path to the *JRE*, which should be used.

GIPPTOOLS_OPTS

You can use this environment variable for additional fine-tuning of the Java runtime environment. It is typically used to set the Java heap size available to GIPPTool programs.

GIPPTOOLS_LEAP

The GIPPTools require up-to-date leap second information to correctly interpret Cube files. Usually, this information is read from the **leap-seconds.list** file located in the **config** subdirectory of the GIPPTools installation directory (**GIPPTOOLS_HOME**). This environment variable can be used to provide a more up-to-date leap second list to GIPPTool programs.

It is usually not necessary to define any of those variables as suitable values should be selected automatically. However, if the automatic detection build into the start script fails, or you need to choose between different GIPPTool or Java runtime releases installed on your computer, these environment variables might become helpful to troubleshoot the situation.

Diagnostics

During execution, the **cube2mseed** utility will produce user feedback. In general, user messages are classified as *INFO*, *WARNING* or *ERROR*.

INFO messages usually report about the progress of the program run, give statistical information or write a final summary. They are only displayed when the `--verbose` command line option is used.

More important are *WARNING* messages. In general, they warn about any issues that may influence the outcome in unexpected ways. Although the program will continue with execution, you certainly should check the results carefully. You might not have gotten what you (thought you) asked for.

Finally, *ERROR* messages inform about problems that cannot be resolved automatically. Program execution usually stops and the user must fix the cause of the error first.

Exit codes

Use the following program exit codes when calling **cube2mseed** from scripts or other programs to see if **cube2mseed** finished successfully. Any non-zero code indicates an *ERROR*!

0

Success.

64

Command line syntax or usage error.

65

Input data was incorrectly formatted.

66

An input file did not exist or was not readable.

70

Error in internal program logic.

74

I/O error.

99

Other, unspecified errors.

Examples

1. To convert all Cube files recorded during an experiment simply use:

```
cube2mseed --verbose --output-dir=./mseed-out/ ./cube-in/
```

The program will recursively search for Cube files inside the cube-in subdirectory. The resulting miniSEED files are written to the mseed-out subdirectory.

While searching for Cube files in the cube-in directory **cube2mseed** will probably complain about files that are not in the expected Cube file format. To get rid of the annoying warnings try the following command line:

```
cube2mseed --verbose --include-pattern=GIPP --output-dir=./mseed-out/ ./cube-in/
```

This will exclude all files not following the usual GIPP naming convention for Cube files. Also, if you are only interested in the data recorded by the Cube with the number 544 you could modify the command line as follows:

```
cube2mseed --verbose --include-pattern='*.544' --output-dir=./mseed-out/ ./cube-in/
```

This works because Cube recorder by default use the unit ID as file extension. You can also repeat include pattern options several times to pick more than one set of files:

```
cube2mseed --verbose --include-pattern='*.544' --include-pattern='*.545' --output-dir=./mseed-out/ ./cube-in/
```

The last command will only process files written by Cube #544 and Cube #545.

2. To convert 30 seconds of Cube data from a single file starting at 1pm on February 16th you would use the following command:

```
cube2mseed --trace-start=2010-02-16T13:00:00 --trace-length=30 --output-dir=./mseed-out/ 02161251.034
```

The program will read from Cube file 02161251.034 from the current working directory and the converted data will be written to the mseed-out subdirectory.

3. You can customize the window width of the *sinc* resampling algorithm.

The following line shows the command line argument necessary to change the window width from the default of 25 to a width of 30:

```
cube2mseed --resample=SINC,30 --output-dir=./mseed-out/ ./cube-in/
```

4. Backward compatibility.

In 2014 the **cube2mseed** was completely rewritten and, besides other things, resampling was added to the utility. Unfortunately, the much improved utility is no longer backward compatible! To partially overcome the deficit, an additional "fake" resampler was implemented that more or less "replicates" the behavior of older GIPPTool releases.

The following command line (applicable to GIPPTool releases 2013.268 and earlier

```
cube2mseed ---time-correction=NONE --output-dir=./mseed-out/ ./cube-in/
```

corresponds to the command line in newer (i.e. after 2014) GIPPTool releases:

```
cube2mseed --timing-control=RULE_BASED --fringe-samples=NOMINAL --resample=NONE  
--output-dir=./mseed-out/ ./cube-in/
```



There is no emulation of the erstwhile *STARTTIME* time correction mode (i.e. the former command line option `--time-correction=STARTTIME`) that also was available in **cube2mseed** utilities released prior to 2014.

Files

`$GIPPTOOLS_HOME/bin/cube2mseed`

The **cube2mseed** "program". Usually just a copy of or a symbolic link pointing to the standard GIPPTools start script.

`$GIPPTOOLS_HOME/bin/gipptools`

The standard start script used to run all GIPPTool utilities.

See also

`gipptools(1)`, `cube2ascii(1)`, `cube2mseed(1)`, `cube2segy(1)`, `cubeaux(1)`, `cubeevent(1)`, `cubeinfo(1)`, `cubeinspect(1)`, `mseed2ascii(1)`, `mseed2mseed(1)`, `mseed2pdas(1)`, `mseed2segy(1)`, `mseedcut(1)`, `mseedinfo(1)`, `mseedrecover(1)`, `mseedrename(1)`

Bugs and caveats

None so far.